



Specification

DN	Measure Range		Working pressure (Bar)	
	Water (L/h)	Air (NL/min)	304SS	PVC
15	30-300	10-100	≤7	≤4
	60-600	20-200		
	90-900	25-250		
20	90-900	20-200		
	120-1200	30-300		
	180-1800	50-500		
25	180-1800	50-500		
	300-3000	100-1000		
	480-4800	150-1500		
32	480-4800	200-2000		
	600-6000	250-2500		
	720-7200	300-3000		
40	1-10m³/h	18-180Nm³/h	≤5	≤3
	1.2-12m³/h	20-200Nm³/h		
	1.5-15m³/h	25-250Nm³/h		
50	1.2-12m³/h	20-200Nm³/h		
	1.5-15m³/h	25-250Nm³/h		
	1.8-18m³/h	30-300Nm³/h		
65	1.8-18m³/h	25-250Nm³/h		
	3-30m³/h	35-350Nm³/h		
	4-40m³/h	40-400Nm³/h		
80	4-40m³/h	40-400Nm³/h		
	5-50m³/h	50-500Nm³/h		
	6-60m³/h	60-600Nm³/h		
100	6-60m³/h	60-600Nm³/h		
	7-70m³/h	70-700Nm³/h		
	10-100m³/h	90-900Nm³/h		

Features:

- Tough glass type meter body with tie-rod on the top & bottom flanges.
- Direct reading permanent scale.
- Flanged or threaded connections in 304SS or PVC
- 304 stainless steel rod guided floats.
- Temperature : PVC ≤ 60°C
304SS ≤ 100°C

Dimensions FA40

	15	20	25	32	40	50	65	80	100	
L	260	340	340	340	340	340	390	390	410	
H	150	200	200	200	200	200	250	250	250	
D	95	105	115	120	130	140	160	190	210	
d	65	75	85	90	100	110	130	150	170	
F	14	14	14	14	14	14	14	18	18	
Weight (kg)	304SS	5	6	8	9	10	14	20	25	30
	PVC	3	3	4	6	7	9	15	13	22

Dimensions VA40

	15	20	25	32	40	50
L	250	300	310	320	330	360
H	150	200	200	200	200	200
D	100	110	120	145	155	170
F	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"

